

Abrasive Cut Off Wheels & Hardware



Oasis

Abrasive Cut Off Wheel

- | | |
|-----------------------------------|---|
| CW40 4"x3/64"x5/8" | CW60 6"x3/64"x7/8" |
| CW450 4-1/2"x3/64"x7/8" | CW70 7"x3/64"x7/8" |
| CW50 5"x3/64"x7/8" | CW14D 14"x 3/32"x 1" Double Reinforced |
| | CW140 14"x 7/16"x 1" |



Oasis Josili

Grinding Wheel

GW45

4-1/2"x1/4"x7/8"

Abrasive Flap Disc Josili/Oasis



- | | |
|--|--|
| F45J4 4-1/2"x7/8" Zirconium 40G | F50J4 5"x7/8" Zirconium 40G |
| F45J6 4-1/2"x7/8" Zirconium 60G | F50J6 5"x7/8" Zirconium 60G |




Weilishi

T27 T29 Abrasive Flap Disc

- | | |
|---------------|-------------------------------|
| F45Z40 | 4-1/2"x7/8" Zirconium 40 Grit |
| F45Z60 | 4-1/2"x7/8" Zirconium 60 Grit |
| F45Z80 | 4-1/2"x7/8" Zirconium 80 Grit |
| F5Z40 | 5"x7/8" Zirconium 40 Grit |
| F5Z60 | 5"x7/8" Zirconium 60 Grit |



Hydraulic Door Closer



HC5014

Spring adjustment nut

- UL listed
- Standard back check function
- Adjustable closing and latching speed (Dual Valve)
- Full spring adjustment from size 1 to 4 for barrier free BF(factory preset size 2)
- Door weight range from 33Lbs to 187Lbs



MAG1100

Electromagnetic Lock AC/DC Adapter & Mounting Hardware


UL Listed
Holding Force: 1100 Lbs
Input: AC120-240V
Output: DC12V(6A)
Lock Body: 10-1/2"x2-7/8"x1-5/8"



LK-EXIT

Size: 42" x 2"

Panic Exit Device w/ Storeroom Keyed Function Lever Trim (UL 500 Series)



PBR

Push Button Quick Release Lock

Adjustable Wall Thickness Up To 11" 25pcs/box